

# KUNSTSTOFF- UND FARBEN-GESELLSCHAFT mbH

An der Flurscheide 7 D-64584 Biebesheim  
Tel. +49 (0) 6258-8006-0 Fax +49 (0) 6258-8006-70  
E-Mail: [info@kfg-biebesheim.de](mailto:info@kfg-biebesheim.de) Internet: [www.kfg-biebesheim.de](http://www.kfg-biebesheim.de)



## Technical Data Sheet

### MMA-Harz V 26

<b>Basic materials:</b>	Methylmethacrylate resin, lightly elastified
<b>Appearance:</b>	blueish, low viscose, turbid liquid
<b>Flashpoint:</b>	+ 10°C (MMA, DIN 51755)
<b>Odour:</b>	ester-like
<b>Viscosity after stirring:</b>	110 ± 20 mPa·s (23°C, Brookfield Spindle 62, 100 rpm)
<b>Viscosity (Efflux time):</b>	30 ± 3 s (23°C, 4mm cup, DIN 53211)
<b>Barcol Hardness:</b>	35
<b>Handling</b>	Breathing protection in case of insufficient ventilation
<b>Curing:</b>	1-1.5 % Dibenzoyl Peroxide 50 %
<b>Curing Time</b>	25-30 min at 23 °C
<b>Pot Life</b>	10 - 15 min at 23°C
<b>Impact strength:</b>	< 25 KJ/m <sup>2</sup>
<b>Cleaning of Tools</b>	Acetone, Methylmethacrylate
<b>Application</b>	binder for lightly elastic sealings
<b>Storage:</b>	up to 6 months when stored cool and dry

Our application technique consulting is not binding. The responsibility for the application resp. the processing of our products is in buyers hand, including property rights of third parties/patent rights. Technical data referring to our products are guide values.  
(updated December 2013)