## KUNSTSTOFF- UND FARBEN-GESELLSCHAFT mbH KFG

An der Flurscheide 7 Tel. +49 (0) 6258-8006-0 D-64584 Biebesheim Fax +49 (0) 6258-8006-70

E-Mail: <u>info@kfg-biebesheim.de</u> Internet: www.kfg-biebesheim.de

## **Technical Data Sheet**

## MMA-Harz B 51

Chemical Basis methylmethacrylate resin with polybutylmethacrylate

**Appearance** bluish, low-viscose, slightly turbid liquid

Flashpoint  $+ 10^{\circ}$ C (MMA, DIN 51755)

**Odour** ester-like

Viscosity 85+/- 20 mPa s (23°C Brookfield Spindle 62, 100 rpm)

**Efflux Time:**  $27 \pm 3 \text{ s } (23^{\circ}\text{C}, 4 \text{ mm cup, DIN } 53211)$ 

**Handling** Breathing protection in case of insufficient ventilation

Curing 2% Dibenzoyl Peroxide 50 %

**Curing Time** 25 - 30 min at 23 °C

**Pot Life** 10- 15 min at 23°C

Cleaning of Tools aceton, methylmethacrylate

**Application** binder for self leveling floor coatings

**Storage** up to 6 months when stored dry and cool

Our application technique consulting is not binding. The responsibility for the application rsp. the processing of our products is in buyers hand, including property rights of third parties/patent rights. Technical data refering to our products are guide values. (updated December 2013)